MULHERN Belting, INC.			Lacing Selection Chart														
	Clip			oper Uniba		bar Alligator		Staple		Bolt Hinged		Rivet Hinged		Bolt Solid Plate		]	
									hickness								
Minimum Pulley Diameter	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
	25SP 25																
15/16"	UCM36SL XSP																
24mm		UCM36SL SP															<u> </u>
	0		25LP														
1-1/2"; 38mm			1														
	UCM36 XS																ļ
	30 UCM36 SP		136 SP														
		36 SP															
		1 XSP															
			30P														
			UX-1 SP RS62														
			UCM36														
2"				36													ļ
51mm			1 SP 7														<u> </u>
					36 LP												
					1												
								-									<b></b>
			U2														<u> </u>
					SP												
						J2											<u> </u>
						2 A3											<u> </u>
2-1/2"; 64mm						15											<u> </u>
					3-1												
				3	-1 RS125												<b> </b>
3"						3-2											<u> </u>
76mm						20											
							3										
							J3	1/2									<u> </u>

		Belt Thickness															
Minimum Pulley Diameter	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
2.0	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
					4-												
4" 102mm						4 1/2-3											
						25 RS187											
								4									
								+ J4									
									1/2								
5"								27									
5 127mm										5							
									L	5							
6"											5						
152mm									-		16						
7"									3	5		7					
175mm																	
6"/152mm									375X								
							R5										
9"/225mm						550											
12"/305mm						R5-1/2											
14"/356mm						140											
18" 450mm			-					190 R6									
															6	<u> </u>	
Minimum	Up to .047" or 3/64"	.063"	.093"	.125" 1/8"	.156"	.187"	.219"	.25"	.281"	.313"	.375"	.406"	.438"	.500" 1/2"	.563"	.625" 5/8"	.688"
Pulley		1/16"	3/32"	,0	5/32"	3/16"	7/32"	1/4"	9/32"	5/16"	11/32"	25/64"	7/16"		9/16"		11/16"
Diameter	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
		Clipper		Unibar		Alligator		Staple		Bolt Hinged		Rivet Hinged		Bolt Solid Plate			